



iQ300, wall-mounted cooker hood, 60 cm, Stainless steel LC67BHM50B



Box design extractor hood with high extraction rate.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ touchControl: quickly and easily manage the power levels and the LED light

Features

Technical Data

Typology : Wall-mounted
Approval certificates : CE, E17D UKCA marking, VDE
Length electrical supply cord : 130 cm
Height of the chimney : 583-912/583-1022 mm
Height of product, without chimney : 53 mm
Minimum distance above an electric hob : 550 mm
Minimum distance above a gas hob : 650 mm
Net weight : 12.3 kg
Type of control : Electronic
Maximum output air extraction : 459 m³/h
Boost position output recirculating : 499 m³/h
Maximum output recirculating air : 404 m³/h
Boost position air extraction : 752 m³/h
Number of lights : 2
Noise level : 64 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable stainless steel
EAN code : 4242003811115
Connection Rating : 255 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation typology : Wall-mounted



4 242003 811115

Optional accessories

LZ50661	Backboard 60 x 72 cm
LZ11FXC56	Clean Air Plus recirc. kit external
LZ10FXJ00	Long Life recirculation kit
LZ10DXU00	Standard recirculation kit
LZ10DXA00	Standard odor filter (replacement)



iQ300, wall-mounted cooker hood, 60 cm, Stainless steel LC67BHM50B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 458 m³/h
 - Intensive 752 m³/h
- Noise max. Normal Level: 64 dB*

Features

- touchControl for extractor speeds and light
- touchControl with Electronic display
- 3 x power levels plus intensive setting
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 x metal grease filter cassettes
- Steel filter cover
- For wall mounted installation

Design

- Chimney hood
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 752 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 64 dB(A) re 1 pW
 - Intensive: 73 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 404 m³/h
 - Intensive: 499 m³/h
 - Noise level in recirculation mode: Max. normal use: 72 dB(A) re 1 pW
 - Intensive: 76 dB(A) re 1 pW
- Power rating: 255 W
- Light Intensity: 242 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 635-1075 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
 - 703 x 600 x 500 mm - mounting with outer chimney
 - 833-1163 x 600 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 60.3 kWh/year*

Optional accessories

- Recirculating kit LZ11DXI16

* In accordance with the EU-Regulation No 65/2014



**iQ300, wall-mounted cooker hood, 60
cm, Stainless steel
LC67BHM50B**

Dimensioned drawings

