| Brand Name | Belling | |
|---|--------------------|-----------|
| Model | BI65FSTA | |
| Number of Oven Cavities | 1 | |
| Cavity Name | Main | |
| Heat source | Electric | |
| Energy Efficiency Index (EEI) | 87.4 | |
| Energy Efficiency Class | A | |
| Energy Consumption per cycle for conventional | / | kWh/cycle |
| Heating function | | |
| Energy Consumption per cycle for forced air | 0.75 | kWh/cycle |
| convection heating function | | |
| Useable Volume | 72 | Litres |
| Rated Voltage/Frequency | 220-240V/50Hz-60Hz | |
| Rated Power | 1900 | W |
| Net Weight | 32.40 | KG |
| Gross Weight | 36.00 | KG |
| Product Dimensions(mm)(W*D*H) | 595x546x596 | MM |
| Carton Dimensions(mm)(W*D*H) | 650x720x671 | MM |
| Packing Dimensions(mm)(W*D*H) | 650x720x671 | MM |

| Brand Name | Belling | |
|---|--------------------|-----------|
| Model | BI65FBLK | |
| Number of Oven Cavities | 1 | |
| Cavity Name | Main | |
| Heat source | Electric | |
| Energy Efficiency Index (EEI) | 87.4 | |
| Energy Efficiency Class | A | |
| Energy Consumption per cycle for conventional Heating function | 1 | kWh/cycle |
| | | |
| Energy Consumption per cycle for forced air convection heating function | 0.75 | kWh/cycle |
| Useable Volume | 72 | Litres |
| Rated Voltage/Frequency | 220-240V/50Hz-60Hz | |
| Rated Power | 1900 | W |
| Net Weight | 31.80 | KG |
| Gross Weight | 35.50 | KG |
| Product Dimensions(mm)(W*D*H) | 595x546x596 | MM |
| Carton Dimensions(mm)(W*D*H) | 650x720x671 | MM |
| Packing Dimensions(mm)(W*D*H) | 650x720x671 | MM |

| Brand Name | Belling | |
|---|--------------------|-----------|
| Model | BI69MFSTA | |
| Number of Oven Cavities | 1 | |
| Cavity Name | Main | |
| Heat source | Electric | |
| Energy Efficiency Index (EEI) | 87.4 | |
| Energy Efficiency Class | A | |
| Energy Consumption per cycle for conventional Heating function | 0.77 | kWh/cycle |
| Energy Consumption per cycle for forced air convection heating function | 0.75 | kWh/cycle |
| Useable Volume | 72 | Litres |
| Rated Voltage/Frequency | 220-240V/50Hz-60Hz | |
| Rated Power | 2300 | W |
| Net Weight | 35.32 | KG |
| Gross Weight | 39.01 | KG |
| Product Dimensions(mm)(W*D*H) | 595x547x596 | MM |
| Carton Dimensions(mm)(W*D*H) | 650x720x671 | MM |
| Packing Dimensions(mm)(W*D*H) | 650x720x671 | MM |

| Brand Name | Belling | |
|---|--------------------|-----------|
| Model | BI69MFBLK | |
| Number of Oven Cavities | 1 | |
| Cavity Name | Main | |
| Heat source | Electric | |
| Energy Efficiency Index (EEI) | 87.4 | |
| Energy Efficiency Class | A | |
| Energy Consumption per cycle for conventional Heating function | 0.77 | kWh/cycle |
| Energy Consumption per cycle for forced air convection heating function | 0.75 | kWh/cycle |
| Useable Volume | 72 | Litres |
| Rated Voltage/Frequency | 220-240V/50Hz-60Hz | |
| Rated Power | 2300 | W |
| Net Weight | 34.22 | KG |
| Gross Weight | 38.81 | KG |
| Product Dimensions(mm)(W*D*H) | 595x547x596 | MM |
| Carton Dimensions(mm)(W*D*H) | 650x720x671 | MM |
| Packing Dimensions(mm)(W*D*H) | 650x720x671 | MM |

| Brand Name | Belling | |
|---|--------------------|-----------|
| Model | BI613MFSTA | |
| Number of Oven Cavities | 1 | |
| Cavity Name | Main | |
| Heat source | Electric | |
| Energy Efficiency Index (EEI) | 79.5 | |
| Energy Efficiency Class | A+ | |
| Energy Consumption per cycle for conventional Heating function | 1.06 | kWh/cycle |
| Energy Consumption per cycle for forced air convection heating function | 0.69 | kWh/cycle |
| Useable Volume | 72 | Litres |
| Rated Voltage/Frequency | 220-240V/50Hz-60Hz | |
| Rated Power | 2900 | W |
| Net Weight | 36.62 | KG |
| Gross Weight | 40.21 | KG |
| Product Dimensions(mm)(W*D*H) | 595x546x596 | MM |
| Carton Dimensions(mm)(W*D*H) | 650x720x671 | MM |
| Packing Dimensions(mm)(W*D*H) | 650x720x671 | MM |

| Brand Name | Belling | |
|---|--------------------|-----------|
| Model | BI613MFBLK | |
| Number of Oven Cavities | 1 | |
| Cavity Name | Main | |
| Heat source | Electric | |
| Energy Efficiency Index (EEI) | 79.5 | |
| Energy Efficiency Class | A+ | |
| Energy Consumption per cycle for conventional | 1.06 | kWh/cycle |
| Heating function | | |
| Energy Consumption per cycle for forced air | 0.69 | kWh/cycle |
| convection heating function | | |
| Useable Volume | 72 | Litres |
| Rated Voltage/Frequency | 220-240V/50Hz-60Hz | |
| Rated Power | 2900 | W |
| Net Weight | 36.61 | KG |
| Gross Weight | 40.20 | KG |
| Product Dimensions(mm)(W*D*H) | 595x546x596 | MM |
| Carton Dimensions(mm)(W*D*H) | 650x720x671 | MM |
| Packing Dimensions(mm)(W*D*H) | 650x720x671 | MM |