



iQ300, canopy cooker hood, 53 cm, Silver metallic LB55565GB

C

The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.

Features

Technical Data

Typology : Built-in/Built-under
Approval certificates : CE, E17D UKCA marking, VDE
Length electrical supply cord : 130 cm
Required niche size for installation (HxWxD) : 255mm x 500.0mm x 350mm mm
Minimum distance above an electric hob : 650 mm
Minimum distance above a gas hob : 650 mm
Net weight : 7.5 kg
Type of control : mechanical
Maximum output air extraction : 363 m³/h
Boost position output recirculating : 395.0 m³/h
Maximum output recirculating air : 268 m³/h
Boost position air extraction : 618 m³/h
Number of lights : 2
Noise level : 56 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242003838396
Connection Rating : 206 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : GB plug
Installation typology : Built-in

Optional accessories

LZ73050 Standard odor filter



4 242003 838396



iQ300, canopy cooker hood, 53 cm, Silver metallic LB55565GB

Features

Key performance features:

- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 618 m³/h
- Noise max. Normal Level: 56 dB*

Features

- Slider switch control for extractor speeds and light
- 3 x power levels plus intensive setting
- Twin motors
- 2 x LED spot 2.15W (low volt)
- Colour Temperature: 3500 K
- 2 x metal grease filter cassettes

Design

- For installation into the base of a wall cupboard
- Canopy hood
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Extraction rate according to EN 61591 Ø 15 cm:
 - max. Normal use 362 m³/h
 - Intensive 618 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 56 dB(A) re 1 pW
 - Intensive: 68 dB(A) re 1 pW
- Power rating: 206 W
- Light Intensity: 438 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 255-255 x 530 x 380 mm
- Dimensions recirculating, chimney (HxWxD): 255-255 x 530 x 380 mm
- Built-in dimensions (HxWxD): 255 x 500 x 350 mm
- Blower Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 79.8 kWh/year*

Optional accessories

- Recirculating kit LZ73050

* In accordance with the EU-Regulation No 65/2014



**iQ300, canopy cooker hood, 53 cm,
Silver metallic
LB55565GB**

Dimensioned drawings

